Lifting Solutions Group
Axel Johnson International

Ferrule K Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

... *Read more*

Material: Aluminum
Marking: According to standard
Standard: Talurit splicing system
The ferrules do not correspond to standard EN 13411-3 but have been tested and verified by Talurit.
Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Ferrule K Talurit®

Technical data

Part code	Ferrule size	Length mm
120100900030	9	36
120101000030	10	41
120101100030	11	45
120101200030	12	50
120101300030	13	55
120101400030	14	59
120101600030	16	64
120101800030	18	73
120102000030	20	82
120102200030	22	91
120102400030	24	100
120102600030	26	109
120102800030	28	118
120103000030	30	127
120103200030	32	136
120103400030	34	146
120103600030	36	155
120103800030	38	164
120104000030	40	173
120104200030	42	182
120104400030	44	191

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved