Lifting Solutions Group
Axel Johnson International

# Ferrule R End stop Talurit®

## Product information



Round ferrule (R) is intended to be pressed on single layer round strand wire ropes, for instance on preventer wires or used as end stop.

The expected strength regarding this end-termination is approximately 50% of the MBL of the wire rope (informative only).

Round aluminium end stops are not recommended for use in high strength applications.

... *Read more*

**Material:** Aluminum
**Note:** See the manufacturer's product data sheet below for guidance on dimension selection.
**Warning:** Ends stops (R) are not allowed to use for lifting applications.

**Certex Latvija**
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Ferrule R End stop Talurit®

## Technical data

| Part code | Ferrule size mm |
|---|---|
| 1205R015 | 1.5 |
| 1205R03 | 3 |
| 1205R04 | 4 |
| 1205R05 | 5 |
| 1205R06 | 6 |
| 1205R065 | 6.5 |
| 1205R07 | 7 |
| 1205R08 | 8 |
| 1205R09 | 9 |
| 1205R10 | 10 |
| 1205R11 | 11 |
| 1205R12 | 12 |
| 1205R13 | 13 |
| 1205R14 | 14 |

**Certex Latvija**
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved