



## Horizontal Lifting Clamp FHX-V

### Product information

For horizontal lifting and transporting of steel plates and other non-deflecting materials. The FHX-V lifting clamp has a spring attached to the cam assembly. The spring makes sure that the clamp will/can be closed and fixed on any desired spot. One of the major advantages of this clamp is that only one person is able to place the clamps and to guide the hoist. FHX-V lifting clamps are only sold in pairs (or multiple pairs).

#### Features:

- Pre-tensioned spring cam feature for easy single operator usage
- Clamp can be closed and fixed on any desired spot
- Compact & lightweight design for easy handling
- Tough quality heavy duty welded body

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

**Temperature range:** - 40°C up to +100°C.

**Standard:** EN 13155

**Note:** Must always be used in pairs (or multiple pairs)

**Warning:** Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm<sup>2</sup>)

Part code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	T mm	H mm	U mm	X mm	Y mm	Weight kg
502100100350680	1 FHX-V	1	0-35	140	99	10	26.5	12	188	85	15	3
502100200600680	2 FHX-V	2	0-60	180	114	15	30.5	19	286	125	16	8
502100300600680	3 FHX-V	3	0-60	200	125	20	30.5	19	302	140	20	12.2
502100400600680	4 FHX-V	4	0-60	220	139	30	30.5	19	316	165	20	17
502100600600680	6 FHX-V	6	0-60	220	139	30	30.5	19	316	165	20	17

## Blueprint

