



## Shortening clutch sling hook, grade 80

### Product information

Hook is equipped with spring loaded safety latch.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part code    | WLL ton | For chain Ø mm | A,   | B, | C, | E, | M mm  | N mm | L   | Ø mm | Weight kg |
|--------------|---------|----------------|------|----|----|----|-------|------|-----|------|-----------|
| 401300110650 | 1.12    | 6              | 8    | 40 | 29 | 20 | 66    | 11   | 136 | 17   | 0.5       |
| 401300200650 | 2       | 7/8            | 10   | 45 | 33 | 27 | 84    | 13   | 172 | 27   | 0.9       |
| 401300320650 | 3.15    | 10             | 12   | 56 | 42 | 33 | 103   | 11   | 215 | 34   | 1.7       |
| 401300530650 | 5.3     | 13             | 15   | 75 | 57 | 40 | 133   | 20   | 258 | 45   | 3.4       |
| 401300800650 | 8       | 16             | 18.5 | 82 | 72 | 44 | 156.7 | 26.5 | 305 | 56   | 5.57      |

# Blueprint

