

Master Link Grab 1 Assy X-A05

Product information



At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Fully integrated shortening hooks and master link.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.


... [Read more](#)

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-4

Safety factor: 4:1
Grade: 10

Master Link Grab 1 Assy X-A05

Blueprint



Technical data

| Part code | Chain diameter mm | WLL ton | WLL 45- 60° ton | WLL 0-45° ton | Can be used to single hook acc | D mm | A mm | B mm | K mm | Weight kg |
|--------------|----------------------|------------|--------------------|------------------|--------------------------------|------|------|------|------|--------------|
| 402100200470 | 6 | 2 | 1,4 | 2 | 4 | 13 | 120 | 70 | 196 | 0.9 |
| 402100350470 | 8 | 3.5 | 2,5 | 3,5 | 6 | 19 | 160 | 95 | 262 | 2.2 |
| 402100560470 | 10 | 5.6 | 4 | 5,6 | 10 | 22 | 170 | 105 | 295 | 3.8 |
| 402100940470 | 13 | 9.4 | 6,7 | 9,4 | 10 | 28 | 190 | 110 | 348 | 7 |
| 402101400470 | 16 | 14 | 10 | 14 | 12 | 32 | 230 | 130 | 432 | 13.6 |