

## Web Sling Connector X-016

---

### Product information



At least 25% greater WLL than traditional Grade 8 products.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.  
Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Tempering temperature minimum 400°C

... [Read more](#)

---

**Material:** Quenched and Tempered Alloy Steel.  
**Marking:** According to standard, Type, manufacturer ID, traceability.  
**Temperature range:** -40° up to +200°C (without reduction in WLL).  
**Finish:** Blue painted.  
**Standard:** EN 1677-1

**Safety factor:** 4:1  
**Grade:** 10

## Web Sling Connector X-016

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	A mm	B mm	D, mm	K mm	Wmm mm	Weight kg
402200140200	6	1.4	15	17	7	56	39	0.2
402200250200	7-8	2.5	18	23	9	63	39	0.3
402200400200	10	4	25	27	11	77	46	0.6
402200670200	13	6.7	30	37	16	97	53	1.1
402201000200	16	10	36	39	19	114	66	2
402201600200	20	16	42	46	22	132	79	3.2
402201900200	22	19	49	59	24	188	124	7.7