



Clevis Self Locking Hook X-026

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Manufactured in accordance with EN 1677-3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and tempered alloy steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	A,	H,	K,	P mm	T mm	Weight kg
402300140730	6	1.4	7	19	94	28	15	0.4
402300250730	7-8	2.5	9	24	119	34	20	0.9
402300400730	10	4	11	30	142	44	26	1.4
402300670730	13	6.7	15	39	178	52	30	3
402301000730	16	10	18	49	213	60	36	5
402301600730	20	16	25	65	251	70	53	11
402301900730	22	19	24	63	273	80	49	13.5

Blueprint

