



## Swivel Self Locking Hook X-027

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Warning:** This hook is a positioning device and is not intended to rotate under load.

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg
420500140940	6	1.4	32	25	12	19	149	28	15	0.7
420500250940	7-8	2.5	36	30	13	24	186	34	20	1.2
420500400940	10	4	41	38	16	30	218	44	26	2
420500670940	13	6.7	46	48	21	39	276	51	30	4.1
420501000940	16	10	61	56	23	49	329	60	36	7.2
420501600940	20	16	74	86	25	65	403	70	53	13
420501900940	22	19	97	98	33	63	455	80	49	20
420502650940	26	26.5	123	120	51	69	535	99	56	33

Blueprint

