

Clevis Sling Hook X-043/S Grade 10

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Clevis Sling Hook X-043/S Grade 10

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	H, mm	K mm	P1 mm mm	T mm	Weight kg
402300140700	6	1.4	7	18	79	23	15	0.3
402300250700	7-8	2.5	9	22	98	27	18	0.6
402300400700	10	4	12	30	122	34	24	1.1
402300670700	13	6.7	15	37	147	44	30	2.3
402301000700	16	10	17	41	166	48	39	3.8
402301600700	20	16	24	64	207	57	48	8.7
402301900700	22	19	25	61	217	73	52	9.5