Round Sling self locking Hook X-028

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Magnaflux crack detection is performed 100% on each batch.

... *Read more*

Material: Quenched and Tempered Alloy Steel
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-3

Safety factor: 4:1
Grade: 10


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Round Sling self locking Hook X-028

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	H mm	K mm	P mm	T mm	W mm	Weight kg
402300140780	6	1.4	19	138	29	15	38	0.6
402300250780	7-8	2.5	24	169	34	20	40	1
402300400780	10	4	30	196	44	26	47	1.8

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved