Lifting Solutions Group
Axel Johnson International

Eye Grip Safe Locking Hook X-950

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-3

Safety factor: 4:1
Grade: 10


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eye Grip Safe Locking Hook X-950

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg
402300400850	10	4	33	13	31	176	49	71	27	137	1.9
402300670850	13	6.7	40	16	39	226	64	80	34	174	4
402301000850	16	10	50	21	47	277	78	114	39	212	6.3

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved