Eye Grip Safe Locking Hook X-950

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-3

Safety factor: 4:1
Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg
402300400850	10	4	33	13	31	176	49	71	27	137	1.9
402300670850	13	6.7	40	16	39	226	64	80	34	174	4
402301000850	16	10	50	21	47	277	78	114	39	212	6.3
402301600850	20	16	62	23	55	329	92	127	54	251	12.3
402302000850	22	19	70	24	59	350	98	151	56	258	14

Blueprint