Lifting Solutions Group
Axel Johnson International

Clevis Grip Safe Locking Hook X-951

Product information



Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard
Temperature range: Tempering temperature minimum 400°C
Standard: EN 1677-3

Safety factor: 4:1
Grade: 10

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Clevis Grip Safe Locking Hook X-951

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg
402300400840	10	4	12.1	31	153	49	71	27	137	1.9
402300670840	13	6.7	15.5	39	203	64	80	34	174	4.1
402301000840	16	10	19.1	47	244	78	114	39	212	7.1

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved