Lifting Solutions Group
Axel Johnson International

Hoist Scaffold DM 200AP

Product information



DM 200AP High performance Scaffold Hoist is designed for use in industrial or construction applications. Can be fitted directly to a standard 48mm scaffold tube in a position to enable it to be rotated through 180 degrees to allow safe loading and unloading by the operator. The front-loading drum for the wire rope reduced the risk of bunching when used on scaffolding that is not perfectly straight.

Features

- Front loading drum
- Power supply 1 phase 220-230V 50Hz
- Pendant control cable length 1,5 – 5,0 m
- Duty Cycle S3 class
- Rope diameter 5mm
- Supplied with 12 months warrant

... *Read more*

Marking: CE-mark
Note: The scaffold bracket/arm is supplied and sold separately.

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Hoist Scaffold DM 200AP

Technical data

Part code	WLL ton	Rope length m	Motor kW	Lifting speed m/min.	Reduction ration	Weight kg
5406DM200AP	0.2	25	0.75	21	1:25	42
5406DM200APVELOX	0.2	40	2.2	38	1:18	43

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved