



Material handling Hoist Red Rooster TCR

Product information

Air chain hoist for material handling 250 kg.

These types Red Rooster Compact pneumatic driven Hoist are very suitable for "Material-Handling". The pendant control is direct on the lower hook so the operator can control and position the load easy and direct. The perfect solution for horizontal movements is the combination with a push trolley.

Standard features:

- Pendant control direct on the lower hook.
- Optimum load control, very precise positioning.
- One-hand control.
- Soft start and stop, no shock movements.
- Handle can be positioned for left-hand or righthand operation.
- Endstop system.

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: CE-marked

Part code	WLL	Lifting	Number	Type	Air consumption	Lowering	Air consumption	Lifting speed	Weight at	Lifting speed	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
	ton	height	of falls		lifting (l/sec)	speed with load	lowering (l/sec)	with max.load	3m HOL	without load	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
		m				m/min		m/min	kg	m/min															
5601TCR250ME	0.25	3	1	TCR-250ME	11.7	16	13	8	11	19	286	174	112	837	15	194	102	92	184	123	61	152	74	78	36

Technical data

Blueprint

