



Material handling Hoist Red Rooster TCR (125 - 250 kg)

Product information

Air chain hoist for material handling.

These types Red Rooster Compact pneumatic driven Hoist are very suitable for "Material-Handling". The pendant control is direct on the lower hook so the operator can control and position the load easy and direct. The perfect solution for horizontal movements is the combination with a push trolley.

Standard features:

- Pendant control direct on the lower hook.
- Optimum load control, very precise positioning.
- One-hand control.
- Soft start and stop, no shock movements.
- Handle can be positioned for left-hand or righthand operation.
- Endstop system.

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: CE-marked

Part code	Code	WLL ton	Lifting height m	Number of falls	Lifting speed without load m/min	Air consumption lifting (l/sec)	Lowering speed with load m/min	Lifting speed with max.load m/min	A mm	B mm	C mm	D mmmmmmm	E mm	F mm	G mm	H mm	I mmmmm	J mm	K mm	L mm	M mm	N mm	O mm	Weight kg
5601TCR125ME	TCR-125ME	0.125	3	1	16	11.7	14	10	286	174	112	837	15	194	102	92	184	13	61	152	74	78	36	11
5601TCR250ME	TCR-250ME	0.25	3	1	16.7	11.7	16.5	8	286	174	112	837	15	194	102	92	184	123	61	152	74	78	36	11

Technical data

Blueprint

