


## Elevator rope 8x19S-FC

### Product information



**General:** Steel wire rope for use in elevator.

**Tolerance:** ≤10 mm 0% – +6%, 10 mm 0% – +5%.

... [Read more](#)

**Rope construction:** 8x19S-FC, Seal.


**Marking:** According to standard

**Finish:** Ungalvanised.

**Standard:** EN 12385-5

**Fill factor:** 0.44

Elevator



## Elevator rope 8x19S-FC

### Technical data

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
106100804130209	8	1,370/1,770	Bright	sZ	28.1	22	SupplierStandard	22.2
106100904130209	9	1,370/1,770	Bright	sZ	35.6	28.3	SupplierStandard	28
106101004130209	10	1,370/1,770	Bright	sZ	44	34.9	SupplierStandard	34
106101104130209	11	1,370/1,770	Bright	sZ	53.2	42.2	SupplierStandard	41
106101204130209	12	1,370/1,770	Bright	sZ	63.3	50.3	SupplierStandard	49
106101304130209	13	1,370/1,770	Bright	sZ	74.3	59	SupplierStandard	58
106101404130209	14	1,370/1,770	Bright	sZ	86.1	68.4	SupplierStandard	67
106101504130209	15	1,370/1,770	Bright	sZ	98.9	78.5	SupplierStandard	77
106101604130209	16	1,370/1,770	Bright	sZ	113	89.3	SupplierStandard	87