Lifting Solutions Group
Axel Johnson International

Boltable lifting eyes

Product information

Boltable lifting eye for lifting. Delivered without bolts. Bolt grade must be min. 8.8
... *Read more*



Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40°C - (+)200°C
Finish: Painted, yellow
Standard: EN 1677-1
Note: No side loading

Safety factor: 4:1


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Boltable lifting eyes

Blueprint



Technical data

Part code	WLL ton	Base dimensions mm	A mm	B mm	D mm	M mm	L mm	E mm	F mm	Weight kg
4215NS8PUL1	1	155 x 51	78	40	12	12.5	155	100	51	1.1
4215NS8PUL2	2	155 x 51	80.5	40	14	14.5	155	100	51	1.2
4215NS8PUL3	3	155 x 51	94	46.5	16	16.5	155	100	51	1.5
4215NS8PUL5	5	180 x 60	118	60	20	22.5	180	120	60	2.6
4215NS8PUL8	8	220 x 62	141	63	26	26.5	220	145	62	4.9

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved