Lifting Solutions Group
Axel Johnson International

Descent device I'D S, Petzl

Product information



The self-breaking Petzl I'D S descender is primarily designed for work at height and rope access work.

Features:

- It has an ergonomic handle that allows comfortable descent control. The integrated anti-panic function and anti-error catch limit the risk of an accident due to user error.
- The AUTO-LOCK system allows users to easily position themselves at a workstation without having to manipulate the handle or tie off the device.
- Once locked, the rope can be taken up without having to manipulate the handle.
- The safety gate allows the rope to be installed with the device remaining connected to the harness.
- It is compatible with 10 to 11.5 mm ropes
- It allows handling of loads up to 250 kg.

... *Read more*

Material: Aluminum, Steel, Nylon
Marking: According to standard, CE-mark
Temperature range: -40°C up to 80°C
Standard: EN 341, EN 12841, EN 15151-1
Warning: Use only technical use life safety ropes. (Core + Sheath)

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Descent device I'D S, Petzl

Technical data

Part code	Max. number of persons	Colour	Rope Ø mm	Weight kg
821500000230	2	Yellow	10 - 11.5	0.6
821500000231	2	Black	10 - 11.5	0.6

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved