

Swageless Terminal with Thread

Product information

Swageless stainless thread terminal for safe, reliable and machine free self assembly.

... [Read more](#)

Material: Stainless steel AISI 316.

Temperature range: -50°C to +100°C and briefly up to +200°C


Finish: High polished.

Warning: Read assembly instructions before use!



Swageless Terminal with Thread

Blueprint



Technical data

| Part code | Rope Ø range mm | MBL ton | Thread | G thread mm | L1 mm | L2 mm | L3 mm | KW1 mm | KW2 mm | Weight kg/100pc |
|------------|-----------------|---------|-----------|-------------|-------|-------|-------|--------|--------|-----------------|
| 1207800305 | 3 | 0.75 | M5 Right | M5 | 79 | 58 | 42 | 10 | 12 | 4.2 |
| 1207810305 | 3 | 0.75 | M5 Left | M5 | 79 | 58 | 42 | 10 | 12 | 4.2 |
| 1207800306 | 3 | 0.75 | M6 Right | M6 | 85 | 63 | 47 | 10 | 12 | 4.5 |
| 1207810306 | 3 | 0.75 | M6 Left | M6 | 85 | 63 | 47 | 10 | 12 | 4.5 |
| 1207800406 | 4 | 1.2 | M6 Right | M6 | 92 | 63 | 47 | 12 | 14 | 5.6 |
| 1207810406 | 4 | 1.2 | M6 Left | M6 | 92 | 63 | 47 | 12 | 14 | 5.6 |
| 1207800408 | 4 | 1.5 | M8 Right | M8 | 102 | 72 | 57 | 12 | 14 | 6.6 |
| 1207810408 | 4 | 1.5 | M8 Left | M8 | 102 | 72 | 57 | 12 | 14 | 6.6 |
| 1207800508 | 5 | 2.18 | M8 Right | M8 | 111 | 78 | 57 | 13 | 16 | 9 |
| 1207810508 | 5 | 2.18 | M8 Left | M8 | 111 | 78 | 57 | 13 | 16 | 9 |
| 1207800510 | 5 | 2.18 | M10 Right | M10 | 117 | 84 | 63 | 13 | 16 | 10 |
| 1207810510 | 5 | 2.18 | M10 Left | M10 | 117 | 84 | 63 | 13 | 16 | 10 |
| 1207800610 | 6 | 3.5 | M10 Right | M10 | 128 | 90 | 63 | 16 | 19 | 15 |
| 1207810610 | 6 | 3.5 | M10 Left | M10 | 128 | 90 | 63 | 16 | 19 | 15 |
| 1207800612 | 6 | 3.7 | M12 Right | M12 | 145 | 107 | 80 | 16 | 19 | 17 |
| 1207810612 | 6 | 3.7 | M12 Left | M12 | 145 | 107 | 80 | 16 | 19 | 17 |
| 1207800712 | 7 | 4.7 | M12 Right | M12 | 153 | 110 | 80 | 18 | 21 | 22 |
| 1207810712 | 7 | 4.7 | M12 Left | M12 | 153 | 110 | 80 | 18 | 21 | 22 |
| 1207800714 | 7 | 4.7 | M14 Right | M14 | 162 | 119 | 89 | 18 | 21 | 25 |
| 1207810714 | 7 | 4.7 | M14 Left | M14 | 162 | 119 | 89 | 18 | 21 | 25 |
| 1207800812 | 8 | 5.1 | M12 Right | M12 | 162 | 113 | 80 | 19 | 24 | 28 |
| 1207810812 | 8 | 5.1 | M12 Left | M12 | 162 | 113 | 80 | 19 | 24 | 28 |

Swageless Terminal with Thread

Technical data

| Part code | Rope Ø range mm | MBL ton | Thread | G thread mm | L1 mm | L2 mm | L3 mm | KW1 mm | KW2 mm | Weight kg/100pc |
|------------|-----------------|---------|-----------|-------------|-------|-------|-------|--------|--------|-----------------|
| 1207800814 | 8 | 5.6 | M14 Right | M14 | 171 | 122 | 89 | 19 | 24 | 31 |
| 1207810814 | 8 | 5.6 | M14 Left | M14 | 171 | 122 | 89 | 19 | 24 | 31 |
| 1207800816 | 8 | 5.6 | M16 Right | M16 | 182 | 133 | 100 | 19 | 24 | 40 |
| 1207810816 | 8 | 5.6 | M16 Left | M16 | 182 | 133 | 100 | 19 | 24 | 40 |
| 1207801016 | 10 | 8.3 | M16 Right | M16 | 190 | 139 | 100 | 24 | 27 | 48 |
| 1207811016 | 10 | 8.3 | M16 Left | M16 | 190 | 139 | 100 | 24 | 27 | 48 |
| 1207801220 | 12 | 12 | M20 Right | M20 | 227 | 159 | 120 | 27 | 32 | 79 |
| 1207811220 | 12 | 12 | M20 Left | M20 | 227 | 159 | 120 | 27 | 32 | 79 |
| 1207801422 | 14 | 17 | M22 Right | M22 | 264 | 191 | 140 | 30 | 36 | 124 |
| 1207811422 | 14 | 17 | M22 Left | M22 | 264 | 191 | 140 | 30 | 36 | 124 |
| 1207801624 | 16 | 21 | M24 Right | M24 | 308 | 227 | 170 | 32 | 41 | 175 |
| 1207811624 | 16 | 21 | M24 Left | M24 | 308 | 227 | 170 | 32 | 41 | 175 |