



Low Headroom Air Chain Hoist Red Rooster TCR

Product information

General: With the LHR series we have a range of trolleys for those applications where a standard trolley headroom is too large. With this special version the hoist is built into the frame of the trolley to decrease the distance of the lower hook to the beam to an absolute minimum.

Standard features:

- State of the art with new drive motor for the trolley
- Low maintenance and wearing of the drive motor through less parts
- Accurate speed control at lifting and lowering
- Accurate speed control of the trolley
- Adjustable to a range of beam sizes

The low head room trolleys are available as standard version (order- number LHATP...) or as spark resistant version with bronze wheels, bronze coated hooks for explosion dangerous areas (order number LHATPSR) with ATEX certificate.

Optional:

- Rack and pinion drive
- Marine paint (with certificate)
- ATEX specifications group II2 & II3

Part Code	WLL ton	Type	Chain falls	Lifting speed without load m/min	Lifting speed with load m/min	Lowering speed with load m/min	Air consumption Hoist	Air consumption Trolley	Weight kg
5601TCR500LHR	0.5	TCR-500-LHR	1	16	10.5	17.9	25	25	85
5601TCR10002LHR	1.1	TCR-1000/2-LHR	2	9.5	5.3	9	25	25	90
5601TCR1000LHR	1.1	TCR-1000-LHR	1	11.3	6	10.3	25	25	90
5601TCR2000LHR	2.2	TCR-2000-LHR	2	5.7	3	5.2	25	25	105