

DynaOne Rope

Product information

Stunt rigging ropes. The naked truth. Pure Dyneema for highest performance with the smallest weight.

Elongation at 10% of breaking load: 0,6%.



Properties:

- Geothane coating for improved protection against weathering and abrasion
- Due to inelastic elongation (creep) under continuous load less suited for static applications
- Very good abrasion resistance
- Excellent UV resistance
- Referring to ISO 10325

... [Read more](#)

Rope construction: 12-braided.

Finish: Grey or anthracite.

DynaOne Rope

Technical data

Part code	Diameter mm	MBL	Breaking load real ton*	Weight kg
301200300000030	3	1	0.9	0.48
301200400000030	4	1.55	1.4	0.84
301200500000030	5	2.66	2.4	1.43
301200600000030	6	3.61	3.25	1.9
301200800000030	8	6.33	5.7	3.3
301201000000030	10	8.83	8.14	4.8
301201200000030	12	13.54	12.19	7.2
301201400000030	14	18.98	17.08	10
301201600000030	16	21.7	19.53	11.5
301201800000030	18	27.53	24.78	15.3
301202000000030	20	34.96	31.46	20.1
301202200000030	22	40.79	36.71	23.4
301202400000030	24	49.52	44.56	28.4
301202600000030	26	54.04	48.64	31
301202800000030	28	64.44	58.89	38.2
301203000000030	30	71.83	64.65	43.4
301203200000030	32	74.1	66.69	46.5
301203400000030	34	84.07	75.66	52.7
301203600000030	36	94.04	84.64	60.1
301203800000030	38	104.52	94.07	66.8
301204000000030	40	107.68	96.91	71.6
301204400000030	44	136.4	122.75	90.7
301204600000030	46	149.56	134.6	99.8
301204800000030	48	157.48	141.74	105.1
301205200000030	52	186.94	168.25	124.6