

## TechnaOne Rope



### Product information

Stunt rigging ropes holds a heap, hardly stretches, doesn't creep at all. Pure aramid as the economical solution for static applications.

**Elongation at 10% of break load:** 0,9%.

#### Properties:

- Available with Geothane coating for high abrasion resistance – or without for a softer finish
- Reasonable UV resistance
- Suited for static applications – even under high temperatures

**Rope construction:** 12-braided.

**Finish:** Black

Part code	Diameter mm	MBL	Breaking load real ton*	Weight kg
301200400000020	4	1.57	1.43	1.1
301200500000020	5	2.58	2.35	2
301200600000020	6	3.65	3.31	2.8
301200800000020	8	6.51	5.91	5
301201000000020	10	10.66	9.69	8
301201200000020	12	15.7	14.28	12
301201400000020	14	19.07	17.34	15
301201600000020	16	24.12	21.92	19.6

301201800000020	18	29.72	37.02	24.8
301202000000020	20	35.89	32.63	30.6
301202200000020	22	42.62	38.75	37
301202400000020	24	49.92	45.38	44
301202600000020	26	58.33	53.03	51.5
301202800000020	28	67.3	61.18	60
301203000000020	30	76.27	69.34	69
301203200000020	32	85.25	77.5	78
301203400000020	34	95.34	86.68	88
301203600000020	36	106.56	96.87	99
301203800000020	38	117.78	107.07	110
301204000000020	40	128.99	117.27	122
301204400000020	44	151.43	137.66	148
301204600000020	46	164.89	149.9	162
301204800000020	48	179.47	163.15	176
301205200000020	52	207.51	188.65	207
301205600000020	56	241.16	219.24	240