Lifting Solutions Group
Axel Johnson International

Sling Hook SHC POWERTEX (with clevis)

Product information



The POWERTEX G10 Sling Hook SHC with Clevis is a Grade 100 lifting hook designed for direct connection to chain sling assemblies and quick attachment to suitable lifting points. The clevis provides a direct connection to the lifting chain, while the solid latch helps retain the load within the hook.

Available for chain sizes from 6 mm to 22 mm with WLLs from 1.4 t to 19 t.

Also available with an eye connection as the Sling Hook SH.

Best used for

- Grade 100 chain sling assemblies requiring a direct clevis connection.
- Applications requiring quick attachment to suitable lifting points.

Not ideal for

- Applications requiring automatic hook locking when loaded. Choose a POWERTEX G10 Self-Locking Hook (SLC) instead.

Product benefits

- Solid latch helps retain the lifting point within the hook.
- Open hook profile enables quick attachment to suitable lifting points.
- Clevis connection enables direct attachment to Grade 100 lifting chain.
- Grade 100 design offers 25% higher WLL than traditional Grade 80 components.
- Conforms to EN 1677 Parts 1, 2, 3 and 4 with a 25% higher WLL.
- Every forged component is crack detection tested. Production samples are proof-load tested, and the design is factory type tested.
- Fatigue tested to 20,000 cycles at 1.5 × WLL with batch traceability and a POWERTEX 2.2 certificate.
- The components may also be used with Grade 8 chain to EN 818-2. In such a case, the chain sling must be rated to Grade 8 in accordance with E

... Read more

Marking: According to standard, POWERTEX + Model (SHC-6-10) + traceability code.
Temperature range: -40°C up to +200°C without reduction in WLL
Finish: Powder painted in red
Standard: EN 1677-2 (+25% WLL), AS 3776

Safety factor: 4:1
Grade: 10


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Sling Hook SHC POWERTEX (with clevis)

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	E mm	H mm	K mm	L mm	M mm	N mm	Weight kg
402300141450	SHC-6-10	6	1.4	8	28.8	18	23	19	79	112	66	15.5	0.3
402300251450	SHC-8-10	8	2.5	9	35	23	27	25	93.5	140	85	20	0.6
402300401450	SHC-10-10	10	4	12	44	25.5	33	28	121	174	103	24	1.2
402300671450	SHC-13-10	13	6.7	15	57	34	40	38	147.6	213.6	133	38	2.3
402301001450	SHC-16-10	16	10	18.5	67	41.5	44	41	166	250	161	41.5	3.8
402301601450	SHC-20-10	20	16	23	80	51	53	50	200	292	187	48	6.8
402301901450	SHC-22-10	22	19	25	97.5	61	72	63	228	339	240	57	10

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved