Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock III-BE

Product information



Stainless steel anchor point ABS-Lock III-BE (Ø 16 mm) is a fall protection solution for flat roofs with a concrete surface (Concrete ≥ C20/25) - is simply hammered into a clean bore hole in less than 2 minutes. Could also be used as a support in a lifeline system.

Force directions: Lateral
Substructure: Concrete
Attachment: Hammered in
Application: Flat roofs

... *Read more*

Material: Stainless Steel
Marking: According to standard, CE-mark, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of users, Serial Nr.
Standard: EN 795, CEN/TS/16415
Note: Install using an installation aid to protect the thread and Data Matrix code

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock III-BE

Technical data

Part code	Max. number of persons	Length mm
8415L3BE300	3	300
8415L3BE400	3	400
8415L3BE500	3	500
8415L3BE600	3	600
8415L3BE700	3	700
8415L3BE800	3	800

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved