
Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock X-H-16

Product information



Stainless steel anchor point ABS-Lock X-H-16 (Ø 16 mm) is a fall protection solution for screwing onto OSB or wooden panelling.
It is equipped with a base plate (200 x 200 mm) and screwed straight onto the wooden panelling using 16 stainless steel screws. Standard package includes 16 high-quality screws and installation set.
Add a supporting tube for usage as an end or corner post in a lifeline system.

Force directions: Lateral
Substructure: Wood
Attachment: Screwed
Application: Flat roofs

... *Read more*

Material: Stainless Steel
Marking: According to standard, CE-mark, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of users, Serial Nr.
Standard: EN 795, CEN/TS/16415

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock X-H-16

Technical data

Part code	Max. number of persons	Length mm
8415LXH15016	3	150
8415LXH30016	3	300
8415LXH40016	3	400
8415LXH50016	3	500
8415LXH60016	3	600

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved