Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock T/-Max

Product information



Stainless steel anchor point ABS-Lock T-Max is a fall protection solution designed for clamping onto the flange of a steel girder without penetrating the surface. It is suitable for all directions of load, can be installed overhead or used as an intermediate bracket in a lifeline system. Included girder clamps made of hot-galvanised steel and all installation materials.

Force directions: Lateral and axial
Substructure: Steel
Attachment: Clamped
Application: Overhead

... *Read more*

Material: Anchor point stainless steel, girder clamps galvanised steel.
Marking: According to standard, CE-mark, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of simultaneous users, Serial Nr.
Standard: EN 795, CEN/TS/16415
Note: ABS-Lock T/-Max for extra-large steel girders

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock T/-Max

Technical data

Part code	Max. number of persons	Flange width mm	Flange depth mm
8415LTMAX	3	270-1370	5-30

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved