Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock Falz IV Standing Seam

Product information



Stainless steel anchor point ABS-Lock Falz IV Standing Seam clamped onto two metal seams - completely penetration-free.
Seam intervals: 300 - 450 mm/420 - 660 mm. This stainless steel anchorage point can be installed on standing seam roofs made of steel, copper, aluminium or titanium zinc without penetrating the roof surface.

Force directions: Lateral
Substructure: Seam roofs, profile roof
Attachment: Clamped, w/o roof penetration
Application: Profile roof, flat roofs

... *Read more*

Material: Stainless Steel
Marking: According to standard, CE-mark, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of users, Serial Nr.
Standard: EN 795, CEN/TS/16415
Note: Incl. installation set.

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock Falz IV Standing Seam

Technical data

Part code	Code	Max. number of persons
8415PF4CU450	PF-4-CU-450	3
8415PF4CU660	PF-4-CU-660	3
8415PF4ST450	PF-4-ST-450	3
8415PF4ST660	PF-4-ST-660	3

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved