

Worm Gear Hand Winch WW250-1500 Painted

Product information



This hand winch is very safe due to the natural braking effect of the worm gear transmission in combination with the load pressure brake. In addition, the winch is easy to use, can be mounted in various ways and has a cable storage up to 120 meters.

- winch suitable for lifting and pulling
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards, downwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- suitable to use with webbing belt W:50 mm D:2 mm (WB)
 belt storage WW250: 10 m
 belt storage WW500 - WW1000: 14 m
- suitable for floor mounting (FM)
- ATEX certified zone 2 and 22 (EX)
 CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
 CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Finish: Standard paint finish (thickness is 60-80 micron in 1 layer) in grey (RAL 7035) and black (RAL 9005) according to DIN 12944, C1M


Standard: EN 13157

Note: Steel, stainless steel, fibre rope (Dyneema) or webbing belt must be ordered separately

Safety factor: 4:1

Worm Gear Hand Winch WW250-1500 Painted

Blueprint



Technical data

| Part code | Code | WLL ton | Rope Ø mm | Rope capacity m | Capacity 1st layer kg | Lifting speed m/min. | Hand force max. kg | WLL Lifting outer layer (kg) | A mm | B mm | C mm | D, G, H, J mm | K mm | L mm | Mmm mm | Nmm mm | Omm mm | Pmm mm | Rmm mm | S mm | Weight kg | | | |
|-----------------|--------|---------|-----------|-----------------|-----------------------|----------------------|--------------------|------------------------------|------|------|------|---------------|------|------|--------|--------|--------|--------|--------|------|-----------|-----|-----|----|
| 501300250000370 | WW250 | 0.25 | 4 | 104 | 250 | 1 | 5 | 92 | 238 | 145 | 100 | 192 | 107 | 105 | 48 | 14 | 160 | 191 | 15 | 365 | 280 | 171 | 132 | 10 |
| 501300050000370 | WW500 | 0.5 | 6 | 78.2 | 500 | 1.2 | 10 | 224 | 269 | 160 | 115 | 223 | 108 | 135 | 70 | 14 | 190 | 221 | 15 | 393 | 325 | 193 | 132 | 13 |
| 501300100000370 | WW1000 | 1 | 8 | 72.5 | 1,000 | 0.8 | 13 | 527 | 302 | 195 | 141 | 254 | 109 | 162 | 102 | 17 | 240 | 266 | 15 | 440 | 350 | 263 | 132 | 22 |
| 501300150000370 | WW1500 | 1.5 | 10 | 41 | 1,500 | 0.5 | 14 | 846 | 302 | 250 | 178 | 254 | 109 | 162 | 102 | 17 | 240 | 278 | 15 | 451 | 350 | 306 | 132 | 24 |