Lifting Solutions Group
Axel Johnson International

Omega link, grade 80

Product information



Omega connecting links are used as terminal fittings in choker chain slings. Omega links also serve as connecting elements (like traditional connecting links) for most master links and eye hooks (with a flat tapered section) and chains of the same nominal size.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Omega link, grade 80

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	T mm	L mm	D mm	K mm	P mm	Weight kg
4012OMEA78	2	7/8	51	68	23	35	10	0.22
4012OMEA10	3.15	10	62	81	31	40	12	0.36
4012OMEA13	5.3	13	80	108	41	54	15	0.71
4012OMEA16	8	16	98	126	49	64	19	1.3

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved