

## Open Wedge Socket OWS B with Bolt



### Product information

Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results.

The wedge socket is delivered complete with wedge, bolt, nut and cotterpin.

2 surface finishes available:

- Model OWS B: blue painted.
- Model OWS BGAL: Hot dipped galvanized.

Model OWS 0.25 and OWS 0.5 only standard available in hot dipped galvanized.

**Material:** Quenched and tempered cast steel.

**Marking:** Size, wire rope diameter and batch or serial number.

**Temperature range:** -40°C to + 110°C - Use at higher temperatures possible with reduction of WLL.

**Finish:** Blue painting or hot dipped galvanized.

**Note:** The efficiency of a 6 and 8 strand wire rope/wedge socket connection is 80% of the minimum breaking load of the wire but limited to the minimum breaking load of the socket (MBL).

Part code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	ØP mm	T mm	TL mm	TB mm	W mm	Weight kg
121500800212	7-8	8	Galvanized	110	18	36	16	9	128	51	18	0.8
121501000212	9-10	12	Galvanized	145	23	46	21	11	168	63	21	1.7
121501300212	11-13	20	Galvanized	157	29	57	25	12	185	67	25	2.1
121501300215	11-13	20	Painted	157	29	57	25	12	185	67	25	2.1
121501600212	14-16	25	Galvanized	190	35	70	30	15	225	85	31	4
121501600215	14-16	25	Painted	190	35	70	30	15	225	85	31	4

121501900212	18-19	40	Galvanized	210	40	80	35	16	250	95	38	7
121501900215	18-19	40	Painted	210	40	80	35	16	250	95	38	7
121502200215	20-22	55	Painted	252	48	95	41	18	300	110	44	10
121502200212	20-22	55	Galvanized	252	48	95	41	18	300	110	44	10
121502600215	23-26	75	Painted	298	55	110	51	22	353	128	51	15
121502600212	23-26	75	Galvanized	298	55	110	51	22	353	128	51	15
121502900215	27-29	90	Painted	322	65	130	57	25	387	142	57	21
121502900212	27-29	90	Galvanized	322	65	130	57	25	387	142	57	21
121503200215	30-32	110	Painted	350	73	146	63	28	423	155	63	31
121503200212	30-32	110	Galvanized	350	73	146	63	28	423	155	63	31
121503600215	34-36	125	Painted	400	74	148	64	28	474	160	70	37
121503600212	34-36	125	Galvanized	400	74	148	64	28	474	160	70	37
121503900212	37-39	150	Galvanized	450	80	142	70	30	530	177	77	51
121503900215	37-39	150	Painted	450	80	142	70	30	530	177	77	51
121504200212	40-42	170	Galvanized	500	87	160	76	33	587	187	76	64
121504200215	40-42	170	Painted	500	87	160	76	33	587	187	76	64

# Blueprint

