



## Master link, grade 80

### Product information

Masterlink for chain sling assemblies.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

<b>Part code</b>	<b>WLL ton</b>	<b>For chain, 1-leg mm</b>	<b>For chain, 2-leg mm</b>	<b>A mm</b>	<b>B mm</b>	<b>D, mm</b>	<b>Weight kg</b>
401100160260	1.6	6/7	6	110	60	13	0.34
401100210260	2.12	8	7	110	60	16	0.53
401100320260	3.15	10	8	135	75	18	0.8
401100530260	5.3	13	10	160	90	22	1.5
401100800260	8	16	13	180	100	26	2.3
401101120260	11.2	18	16	200	110	32	3.9
401101400260	14	20	18	260	140	36	6.35
401101700260	17	22	20	300	160	40	9
401102120260	21.2	26	22	340	180	45	12.8
401103150260	31.5	32	26	350	190	50	17.2
401104500260	45	36	32	400	200	56	24.2

# Blueprint

