Lifting Solutions Group
Axel Johnson International

Eye grab hook, grade 80

Product information

Eye grab hook is used for shortening chain legs of a sling. The grab hook is attached to the master link with the same connection link as the chain. ... *Read more*



Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eye grab hook, grade 80

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	A mm	K mm	P mm	Weight kg
4013LYK6	1.12	6	13,5	49	8	0.14
4013LYK78	2	7-8	17	59,5	11	0.245
4013LYK10	3.15	10	20	77,5	13	0.65
4013LYK13	5.3	13	26	97,5	16,5	1.39
4013LYK16	8	16	30	106	19	2.2
4013LYK20	12.5	20	37	140	24	4.6
4013LYK22	15	22	44	162	28	8.2
4013LYK26	21.2	26	49	193,5	30	9.8
4013LYK32	31.5	32	57	227	38	19.4

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved