# Wire Rope Lifting Sling WLS-264

## Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2**
**Design:** Master link in one end and soft eyes in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye lengths with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

| Part Code | WLL ton |
|---|---|
| 1605 | 0.16 |
| 1605 | 0.29 |
| 1605 | 0.45 |
| 1605 | 0.66 |
| 1605 | 0.89 |
| 1605 | 1.15 |
| 1605 | 1.45 |
| 1605 | 1.79 |

| | | |
|---|---|---|
| | 1605 | 2.17 |
| | 1605 | 2.57 |
| | 1605 | 3.03 |
| | 1605 | 3.52 |
| | 1605 | 4.6 |
| | 1605 | 5.81 |
| | 1605 | 7.17 |
| | 1605 | 8.69 |
| | 1605 | 10.33 |
| | 1605 | 12.13 |
| | 1605 | 14.06 |
| | 1605 | 18.37 |
| | 1605 | 23.23 |
| | 1605 | 28.78 |
| | 1605 | 34.69 |
| | 1605 | 41.37 |

## Technical data