Lifting Solutions Group
Axel Johnson International

Lifting Eye RUD VLBG

Product information



- Captive but exchangable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads

... *Read more*

Temperature range: -40°C up to +100°C.

Safety factor: 4:1

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Eye RUD VLBG

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	M mm	N mm	T mm	Weight kg
42158600399	VLBG-M14	1.2	33	56	36	30	39	13.5	36	21	86	47	57	M14	38	85	0.52
42158600384	VLBG-M18	2	50	82	54	45	55	16.5	43	27	113	64	70	M18	48	110	1.3
42158600385	VLBG-M22	2.5	50	82	54	45	54	16.5	43	33	113	64	75	M22	48	110	1.31
42157983658	VLBG-M27	4	60	103	65	60	69	22.5	61	39	151	80	100	M27	67	147	3.07

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved