



Levelling Tool Ganterud

Product information

This electric levelling tool levels and handles loads efficiently and safely. Due to its high degree of precision, the work becomes more efficient. This reduces both expensive crane time and waiting times. The levelling tool is operated with a user-friendly, IP67-rated remote control.

The Pro models do also offer auto levelling functionality with released chain wheel which makes it easy to find the centre of gravity of the lifted object. Snatch block function with released chain wheel makes rotation of items easy, quick, and safe.

Environmental requirements:

- Storage temperature: -20°C up to +45°C
- Relative humidity (RH): 0 – 90% when stored
- IP rating: IP65

Handheld controller:

- Number of function keys: 5/7 for Pro models
- Power output: 10 mW
- Power supply: 3X1,5V AAA
- IP rating: IP67

Optional equipment:

- Protective cover
- Extended chain
- Extra batteries
- Transport packaging

Marking: According to standard, CE-marked

Temperature range: -20°C up to +40°C

Standard: EN 13155

Part code	Code	WLL	Width	Height	Chain size	Chain length	Depth	Load imbalance capacity max.	Reversible stroke pr. hook	Max. leveling length	Weight
		ton	mm	mm	mm	m	mm	kg	m	m	kg
6205L3	L3 mm	3	503	639	30.5x10	3	495	500	1.5	3 (1,5 + 1,5)	126
6205L5	L5 mm	5	503	639	30.5x10	3	495	750	1.5	3 (1,5 + 1,5)	139
6205L5PRO	L5 PRO	5	503	639	30.5x10	3	495	750	1.5	3 (1,5 + 1,5)	139
6205L10HeavyDuty	L10 Heavy Duty	10	-	-	-	3	-	4,000	1.5	3 (1,5 + 1,5)	180
6205L12PRO	L12 PRO	12	740	750	48x16	4	595	2,500	2	4 (2+2)	295
6205L203PRO	L20-3 PRO	20	712	1,050	60.5x20	6	623	3,000	3	6 (3+3)	395