



Lifting Eye RUD VRS-F Starpoint, UNC thread

Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

Marking: CE-marked

Safety factor: 4:1

Part code	WLL ton	B,	C,	D,	E,	G,	I mm	K,	L	N mm	T mm	Weight kg
421100030740	0.3	11	9	25	25	30	16.3	47	12	7.94	35	0.13
421100040740	0.4	11	9	25	25	30	16.3	47	15	6.35	35	0.12
421100040745	0.4	11	9	25	25	30	16.3	47	15	6.35	35	0.12
421100080740	0.75	13	10	30	30	34	19.8	56	19	7.94	42	0.22
421100150740	1.5	15	13	35	36	40	23.5	65	24	9.53	49	0.33
421100230740	2.3	17	16	40	41	50	29.3	76	29	12.7	58	0.58
421100230745	2.3	17	16	40	41	50	29.3	76	33	12.7	58	0.61
421100320740	3.2	20	19	49	51	60	35	92	36	14.29	70	0.98
421100320745	3.2	20	19	49	51	60	35	92	36	9/16"	70	1
421100320746	3.2	20	19	49	51	60	35	92	36	9/16"	70	1
421100450740	4.5	26	24	60	66	75	44	114	48	15.88	87	2.08
421100700740	7	32	29	73	76	98	53	135	54	22.23	104	3.6
421100900740	9	37	33	84	86	111	62	158	63	25.4	121	4.95
421101200740	12	42	42	94	100	128	70	180	72	28.58	138	7.6

Technical data

Working load limit in metric tons

RUD Load table VRS, VRS-F

Blueprint

