Lifting Eye RUD VWBG-V, UNC thread

Product information



- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing

... *Read more*

Marking: According to standard
Temperature range: -40°C up to +100°C
Standard: EN 1677-1

Safety factor: 4:1


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Eye RUD VWBG-V, UNC thread

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	T mm	Weight kg
42157991090	0.3	8	31	29	30	27	13	36	76	0.18
42157991091	0.45	8	31	29	33.5	30	17	38	78	0.29
42157991092	0.6	10	49	35	42	36	21	47	107	0.41
42157991093	1.3	13	46	38	48	41	29	56	114	0.7
42157991094	2	13	54	35	62	55	28	67	137	1.42
42157991095	3.5	18	66	40	81	70	40	88	173	2.63
42157991096	5	22	90	50	99	85	47	106	221	5.09

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved