

Lifting Eye Bolt RUD RS, UNC/UN thread

Product information



- considerably higher WLL in comparison to DIN 580
- clear marking of the minimum WLL
- comprehensive range of threads


... [Read more](#)

Marking: According to standard
Temperature range: -40°C up to +200°C
Standard: EN 1677-1

Safety factor: 4:1

Lifting Eye Bolt RUD RS, UNC/UN thread

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	T mm	Weight kg
421100010722	0.1	12	11	10	25	25	34	0.1
421100020720	0.2	12	11	10	25	25	34	0.1
421102500720	0.25	15	11	10	25	25	34	0.1
421104000720	0.4	18	13	12	30	30	41	0.18
421104000725	0.4	18	13	12	30	30	41	0.18
421107500720	0.75	22	15	14	35	35	48	0.3
421100100720	1	24	15	14	35	35	48	0.3
421100120720	1.2	30	17	16	40	40	55	0.47
421100150720	1.5	34	21	20	50	50	70	0.8
421100200720	2	36	21	20	50	50	70	0.85
421100250720	2.5	45	26	24	60	60	85	1.6
421100250725	2.5	45	26	24	60	60	85	1.6
421100300720	3	46	26	24	60	60	85	1.6
421100300725	3	45	26	24	60	60	85	1.6
421100300726	3	55	43	38	90	100	130	6.1
421100400720	4	58	43	38	90	100	130	6.2
421100400725	4	58	43	38	90	100	130	6.5
421100600720	6	67	43	38	90	100	130	6.3
421100600725	6	67	43	38	90	100	130	6.5
421100800720	8	67	43	38	90	100	130	6.5