

Lifting Eye VLBG-Z RUD, UNC with variable length

Product information



- Captive but exchangeable RUD-Bolt
- Bracket adjustable in force direction
- Comprehensive range of threads


... [Read more](#)

Temperature range: -40°C up to +100°C

Safety factor: 4:1

Lifting Eye VLBG-Z RUD, UNC with variable length

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	lmm mm	K mm	L mm	Nmm mm	T mm
421100061180	0.63	30	54	34	24	39	10	29	10-98	75	45	39-127	32	75
421100101180	1	32	54	34	26	38	10	29	13-123	75	45	42-152	32	75
421100151180	1.5	33	56	36	30	39	13.5	36	16-148	86	47	52-184	38	85
421100251180	2.5	50	82	54	45	55	16.5	43	19-185	113	64	62-228	48	110
421100251185	2.5	50	82	54	45	55	16.5	43	22-211	113	64	65-254	48	110
421100401180	4	50	82	54	45	67	18	43	25-211	130	78	68-254	48	125
421100501180	5	60	103	65	60	64	22.5	61	32-278	151	80	93-339	67	147
421100801180	8	77	122	82	70	97	26.5	77	38-270	205	110	115-347	87	197
421102001180	20	95	156	100	95	105	36	87	51-302	230	130	138-389	100	222