


Steel Wire Rope 6x19-WSC Seal

Product information



ISO 4309 Rope Category No: All Diameters RCN.02

... [Read more](#)

Rope construction: 6x19-WSC Seale.

Marking: According to standard

Standard: EN 12385-4

RCN: 02

Slings




Winch rope



Stay rope



Overhead cranes



Steel Wire Rope 6x19-WSC Seal

Technical data

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
101100604250210	6	1,770	Galvanized	sZ	22.7	16.2	Dry	14.4
101100604270210	6	1,960	Galvanized	sZ	25.1	16.2	Dry	14.4
101100704250210	7	1,770	Galvanized	sZ	30.9	22	Dry	19.6
101100704270210	7	1,960	Galvanized	sZ	34.2	22	Dry	19.6
101100804250210	8	1,770	Galvanized	sZ	40.3	28.7	Dry	25.6
101100804270210	8	1,960	Galvanized	sZ	44.7	28.7	Dry	25.6
101100904250210	9	1,770	Galvanized	sZ	51	36.4	Dry	32.4
101100904270210	9	1,960	Galvanized	sZ	56.5	36.4	Dry	32.4
101101004250210	10	1,770	Galvanized	sZ	63	44.9	Dry	40
101101004270210	10	1,960	Galvanized	sZ	69.8	44.9	Dry	40
101101104250210	11	1,770	Galvanized	sZ	76.2	54.3	Dry	48.4
101101104270210	11	1,960	Galvanized	sZ	84.4	54.3	Dry	48.4
101101204250210	12	1,770	Galvanized	sZ	90.7	64.7	Dry	57.6
101101204270210	12	1,960	Galvanized	sZ	101	64.7	Dry	57.6