Lifting Solutions Group
Axel Johnson International

Tower / Derrick Hoist Block McKissick M-491

Product information



Suitable for hoisting personnel, contingent upon all employees, including the winch operator, being trained to follow any applicable Federal, local and industry standards.

Design: Recessed sideplates design reduces the gap between the sheave rim and the sideplate. Sealed tapered roller bearings. Shackle fitting swivels for easy positionering. Holes through side plate are available for secondary block securement device.

... *Read more*

Material: Forged steel swivels, tees, yokes and shackles are Quenched & Tempered
Marking: CE-mark, WLL
Finish: Painted

Safety factor: 4:1

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Tower / Derrick Hoist Block McKissick M-491

Technical data

Part code	Rope Ø range mm	WLL ton	Sheave dia mm	Weight kg
424100400280	10-13	4	203	16
424100800280	10-13	8	254	25
424100800285	13-14	8	254	25
424101200280	13-14	12	254	25
424101200285	13-16	12	356	43
424101200286	16-19	12	356	43
424101500280	19-22	15	406	68
424101500285	22-26	15	406	48
424102500280	26-29	25	457	118
424103000280	29-32	30	508	306

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved