



Round Sling EXTREEMA® XS

Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m
- Standard with RFID

Material: HMPE -Dyneema®

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	EWL m	Colour
340500300050030	3	0.5	Yellow
340500300080030	3	0.75	Yellow
340500300100030	3	1	Yellow
340500300150030	3	1.5	Yellow
340500300200030	3	2	Yellow
340500300250030	3	2.5	Yellow
340500300300030	3	3	Yellow
340500300400030	3	4	Yellow
340500300500030	3	5	Yellow
340500300380030	3	3.75	Yellow
340500300600030	3	6	Yellow
340500300280030	3	2.8	Yellow
340500300700030	3	7	Yellow
340500300800030	3	8	Yellow
340500500050030	5	0.5	Red
340500500100030	5	1	Red
340500500150030	5	1.5	Red
340500500200030	5	2	Red
340500500250030	5	2.5	Red
340500500300030	5	3	Red
340500500400030	5	4	Red
340500500500030	5	5	Red

340500500080030	5	0.75	Red
340500500600030	5	6	Red
340500500700030	5	7	Red
340500500800030	5	8	Red
340501000150030	10	1.5	Orange
340501000200030	10	2	Orange
340501000300030	10	3	Orange
340501000400030	10	4	Orange
340501000500030	10	5	Orange
340501000100030	10	1	Orange
340501000250030	10	2.5	Orange
340501001250030	10	12.5	Orange
340501001000030	10	10	Orange
340501000800030	10	8	Orange
340501000600030	10	6	Orange
340501000050030	10	0.5	Orange
340501000700030	10	7	Orange
340501500500030	15	5	Orange

Technical data

		Extreema® XS roundsling		
		HMPE EXS		
WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50