

## Horizontal Lifting Clamp TNMH

---

### Product information



For horizontal lifting and transporting of all non-deflecting plates and structures without marking, scratching and or damaging the material surface.

Perfect for lifting materials such as (stainless) steel, aluminum, nature stone, composite, painted materials, wood, glass, plastic, etc .

Jaw openings available from: 0 to 50 mm

#### Features:

- Jaw and cam are covered with a special high quality pressure resistant fabric
- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... [Read more](#)

---

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.


**Temperature range:** - 40°C to +50°C.

**Standard:** EN 13155

**Note:** Must always be used in pairs (or multiple pairs)

## Horizontal Lifting Clamp TNMH

### Blueprint



### Technical data

Part code	Code	WLL ton	Jaw width mm	H, mm	S mm	T mm	U mm mm	V mm mm	Wmm mm	X mm mm	Ymm mm	Weight kg
502100100251610	1 TNMH	1	0-25	10	94	20	155	140	15	65	15	2.4
502100200451610	2 TNMH	2	0-45	15	151	30.5	267	225	23	90	15	7.5
502100300451610	3 TNMH	3	0-45	15	151	30.5	271	225	20	90	15	8.3
502100400501610	4 TNMH	4	0-50	17.5	161	30.5	300	250	20	115	30	13
502100600501610	6 TNMH	6	0-50	17.5	161	30.5	306	250	25	130	30	18