


Chain Hoist Elephant HOISTMAN

Product information



The Elephant HOISTMAN is a lightweight mini-hand chain hoist. Very compact for use in confined spaces and where a low self weight is desirable.

Features

- Steel chromed body.
- Little operating effort at maximum load due to bearing shafts.
- Double pawl system.
- Self-locking brake that holds the load at any desired height.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 10).
- Galvanized hand chain

Standard delivery


- 2,5 meters lifting height (maximum distance between top and bottom hook).
- 2 meters operating height.

... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 13157, EN 818-7

Chain Hoist Elephant HOISTMAN

Blueprint



Chain Hoist Elephant HOISTMAN

Technical data

Part code	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	Weight kg
500100020250900	0.15	2.5	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	2.8
500100020400900	0.15	4	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	3.5
500100020500900	0.15	5	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	4
500100020600900	0.15	6	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	4.5
500100020700900	0.15	7	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	5
500100020800900	0.15	8	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	5.5
500100020900900	0.15	9	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	6
500100021000900	0.15	10	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	6.5
500100030250900	0.25	2.5	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	2.8
500100030400900	0.25	4	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	3.5
500100030500900	0.25	5	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	4
500100030600900	0.25	6	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	4.5
500100030700900	0.25	7	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	5
500100030800900	0.25	8	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	5.5
500100030900900	0.25	9	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	6
500100031000900	0.25	10	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	6.5