

## Lifting Point Pewag PLZW-rapid

### Product information



The PLZW-rapid is a lifting point distinguished by its innovative features. It allows for quick and easy assembly: simply press the button to unlock the threaded plates, insert the lifting point into the threaded hole, release the button, and tighten the screw by hand. The locking indicator must then be checked to ensure the green ring is visible, confirming the lifting point is ready for use.

Designed for maximum flexibility, the PLZW-rapid is 360° rotatable, allowing for adjustment in the direction of the load, and the ring can be folded 180° for added versatility. The screw is made of rust-resistant stainless steel, while the sleeve protects the contact surface of the load. Each unit features an individual serial number for traceability and offers a five-fold safety factor against breakage. [... Read more](#)

**Material:** Alloy steel, stainless steel

**Marking:** According to standard, CE-marked, WLL, thread size and an individual serial number.

**Temperature range:** -20°C up to +200°C

**Standard:** EN 1677-1  
*except grade/WLL*

**Safety factor:** 5:1

## Lifting Point Pewag PLZW-rapid

### Blueprint



### Technical data

Part code	Code	WLL ton	Thread mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	h mm mm	n mm mm	Weight kg
42154106202	PLZW-R 0.4t	0.4	M10	40	64	14	33	77	30	30	20	0.3
42154106204	PLZW-R 0.5t	0.5	M12	40	64	14	33	77	30	30	23	0.3
42154106205	PLZW-R 1.1t	1.1	M16	50	83	19	53	112	45	41	24	0.85