

## Spur Gear Hand Winch TL1500 SST Stainless

### Product information



This spur gear winch is fast, easy and can be mounted on both walls and floors. The free spool option is therefore also available for this winch.

- robust and safe lifting and pulling winch
- protection classification IP54
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards, downwards or at the left
- closed gearbox to protect against environmental influence
- adjustable crank
- suitable for wall and floor mounting
- Stainless steel 304

#### Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- stainless steel grade 304 (SST304)
- 2 drum compartment (2D)
- free-spooling device for pulling applications. To disengage the drum (FS)
- ATEX certified zone 2 and 22 (EX)

CE II 3G Ex IIC T4 Gc, -20°C < T amb < +70°C

CE II 3D Ex IIIC T135°C Dc, -20°C < T amb < +70°C

... [Read more](#)

**Material:** Stainless steel 304

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +70°C


**Standard:** EN 13157

**Note:** The cable must be ordered separately, ask for more information about our sales

**Safety factor:** 4:1

## Spur Gear Hand Winch TL1500 SST Stainless

### Blueprint



### Technical data

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight kg
501300150001060	TL1500 SST	1.5	10	21	1,500	927	27.5