

Swivel Davit Crane SD750 SST316

Product information



With three adjustable positions, this crane effortlessly adapts to your lifting needs. Depending on the position, the lifting capacity varies; up to 750 kg at 1 meter, 600 kg at 1,5 meters and 500 kg at 2 meters.

Thanks to the 360 degree rotation function, you can easily reach the desired position. When in position you can lock the swivel motion for controlled lifting and lowering. The stainless steel 316 finish ensures durability, while you can attach various winches or even a chain hoist to the davit. Ideal for any project where strength and flexibility come together!

- adjustable reach: 1 meter, 1,5 meters and 2 meters
- robust and safe lifting davit crane in compliance with EN13157
- possible to lock swivel motion
- davit crane consists of 4 parts - fast installation
- possible to rotate 360° with arm, or belt on end of boom
- possible to mount different winches on crane: CW700 & TL1500
- Standard stainless steel 316. CW700 SST316 & TL1500 SST304

Options:

- 40 cm height extension
- ATEX certified zone 2 and 22 (EX)
 - CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
 - CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... [Read more](#)

Material: Stainless steel


Marking: According to standard, CE-marked

Standard: EN 13157

Note: WLL and lifting speed with winch TL1500

Swivel Davit Crane SD750 SST316

Blueprint



Technical data

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Lifting speed m/min.	Weight kg
601177002011	SD750 SST316	0.75	8	33	1.2	49