

Lifting Eye Theipa Point - F

Product information



The THEIPA Point-F internal thread attachment swivel is a ball-bearing lifting attachment point for industrial load handling. It is used where a swivel connection with internal thread is required, helping maintain correct load alignment while reducing the risk of link kinking through its crimped link design.

Best used for:

- Swiveling lifting points with internal thread connection.
- Applications requiring galvanized corrosion protection.

Product benefits:

- Ball bearing supports controlled swivel movement under load.
- Crimped link helps prevent kinking during handling.
- Galvanized coating provides corrosion protection.
- Multiple thread sizes support different load requirements.
- RFID chip option supports digital identification.

Different threaded versions and lengths can be supplied on request

[... Read more](#)

Material: Eye and swivel of alloy

Marking: CE-marked, UKCA-marked, WLL.


Temperature range: -40° up to +400°C

Finish: Painted.

Safety factor: 4:1

Lifting Eye Theipa Point - F

Blueprint



Kind of attachment



Number of pieces

1

1

2

2

2

2

3 o. 4

3 o. 4

Inclination angle

0°

90°

0°

90°

0°-45°

45°-60°

0°-45°

45°-60°

WLL

WLL

WLL

WLL

WLL

WLL

WLL

WLL

Code

 Thread
version

t

t

t

t

t

t

t

t

TP-F 0,5

M 12 x 15

1,4

0,5

2,8

1,0

0,7

0,5

1,0

0,75

TP-F 1

M 16 x 20

2,8

1,0

5,6

2,0

1,4

1,0

2,12

1,5

TP-F 1,7

M 20 x 25

5,0

1,7

10,0

3,4

2,4

1,7

3,55

2,5

TP-F 2,1

M 24 x 30

8,0

2,1

16,0

4,0

2,8

2,1

4,25

3,15

TP-F 3,2

M 30 x 40

12,0

3,2

24,0

6,4

4,25

3,15

6,7

4,75

TP-F 5

M 36 x 45

15,0

5,0

30,0

10,0

6,7

5,0

10,0

7,5