Lifting Solutions Group
Axel Johnson International

Weld-on Lifting Point TAPSK

Product information



The TAPSK edge fastening is a weld-on sling point for creating lifting attachment points on machine, steelwork, or load edges. It is used where a compact welded connection and a movable D-link are required, with working load limits from 3.15 to 8 t.

Best used for:

- Welded edge attachment points on industrial loads.
- Applications needing a D-link with 270° movement.

Product benefits:

- Compact design supports installation on edge fastening points.
- D-link swings 270° for flexible load connection.
- Weld-on block in S355J2, in accordance with EN 10025.
- Four-times secured design supports controlled lifting use.
- RFID chip available for simplified identification.

... *Read more*

Features: 180º swing.
Marking: CE-mark, UKCA-marked
Finish: Red painted.

Safety factor: 4:1
Grade: 8

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Weld-on Lifting Point TAPSK

Blueprint



Kind of attachment							
Number of pieces	**1**	**1**	**2**	**2**	**2**	**3 o. 4**	**3 o. 4**
Inclination angle	**0°**	**0°**	**0°**	**0°-45°**	**45°-60°**	**0°-45°**	**45°-60°**
	WLL	**WLL**	**WLL**	**WLL**	**WLL**	**WLL**	**WLL**
Code	**t**	**t**	**t**	**t**	**t**	**t**	**t**
TAPSK 3	3,15	3,15	6,3	4,45	3,15	6,7	4,75
TAPSK 5	5,3	5,3	10,6	7,5	5,3	11,2	8
TAPSK 8	8	8	16,0	11,2	8	17	11,8

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved